



MADE IN USA

REICHdrill[®]

QUALITY DRILLING EQUIPMENT



The **T-650-W LEGEND 3**

RECOMMENDED HOLE SIZE: 4 ½ in. – 8 in. (114 – 204 mm)
MAXIMUM RECOMMENDED DEPTH: 1000 ft. (312 m)
DRILL PIPE CAPACITY: 640 ft. of 3 ½ in. or 540 ft. of 4 in.
MAXIMUM RATED PULLBACK: 28,000 lbs. (12,700 kg)
MAXIMUM RATED PULLDOWN: 15,500 lbs. (7,030 kg)
HEAD TRAVEL: Std – 24 ft. (7.5 m) Opt. – 28 ft. (8.5 m)
STANDARD ROTATION & TORQUE: 0 – 108 RPM @ 57,200 lb-in. (6463 Nm)
Approximate Operating Weight: 52,000 lbs. (23,587 kg)
APPROXIMATE BARE MACHINE WEIGHT: 52,000 lbs. (23,587 kg)

AIR COMPRESSOR & ENGINE

- **STD:** 900 CFM @ 350 PSI @ 1800 RPM (25.5 m³/min @ 24 Bar) w/ 475 HP (354 kW) CAT C13 ACERT
- **OPT:** 1000CFM @ 350 PSI @ 2100 RPM (28.3 m³/min @ 24 Bar) w/ 540 HP (403 kW) CAT C15 ACERT
- **OPT:** 1070CFM @ 375 PSI @ 1800 RPM (30.3 m³/min @ 25.8 Bar) w/ 580 HP (433 kW) CAT C15 ACERT

AIR COMPRESSOR 900 CFM (25.5 m³/min) @ 350 PSI (24 Bar) with an Air Pressure Regulator is standard.

OPTIONAL EQUIPMENT

- Dual speed and torque rotary heads
- Compressor variable volume control
- Four leveling jack system