



MADE
IN USA

REICHdrill[®]
QUALITY DRILLING EQUIPMENT



The T-650-W LEGEND 5

RECOMMENDED HOLE SIZE: 5 in. – 8 3/4 in. (127 – 223 mm)

MAXIMUM RECOMMENDED DEPTH: 2500 ft. (762 m)

DRILL PIPE CAPACITY: 540 ft. of 4 in. or 480 ft. of 4 ½ in.

MAXIMUM RATED PULLBACK: 55,000 lbs. (24,948 kg)

MAXIMUM RATED PULLDOWN: 27,000 lbs. (12,247 kg)

HEAD TRAVEL: 28 ft. (8.5 m)

STANDARD ROTATION & TORQUE: 0 – 108 RPM @ 85,795 lb-in. (9,695 Nm)

Approximate Operating Weight: 60,000 lbs. (27,216 kg)

AIR COMPRESSOR & ENGINE

- **STD:** 900 CFM @ 350 PSI @ 1800 RPM (25.5 m³/min @ 24 Bar) w/ 540 HP (403 kW)
CAT C15 ACERT
- **OPT:** 1000CFM @ 350 PSI @ 2100 RPM (28.3 m³/min @ 24 Bar) w/ 540 HP (403 kW)
CAT C15 ACERT
- **OPT:** 1070CFM @ 375 PSI @ 1800 RPM (30.3 m³/min @ 25.8 Bar) w/ 580 HP (433 kW)
CAT C15 ACERT

AIR COMPRESSOR 900 CFM (25.5 m³/min) @ 350 PSI (24 Bar) with an Air; Pressure Regulator is standard.

OPTIONAL EQUIPMENT

- Dual speed and torque rotary heads
- Compressor variable volume control
- Four leveling jack system