



MADE IN USA

REICHdrill®

QUALITY DRILLING EQUIPMENT



The **T-650-W LEGEND 6**

- RECOMMENDED HOLE SIZE:** 5 in. – 10 in. (127 – 254 mm)
- MAXIMUM RECOMMENDED DEPTH:** 2500 ft. (762 m)
- DRILL PIPE CAPACITY:** 540 ft. of 4 in. or 480 ft. of 4 ½ in.
- MAXIMUM RATED PULLBACK:** 55,000 lbs. (24,948 kg)
- MAXIMUM RATED PULLDOWN:** 30,000 lbs. (13,608 kg)
- HEAD TRAVEL:** 28 ft. (8.5 m)
- STANDARD ROTATION & TORQUE:** 0 – 106 RPM @ 85,795 lb-in. (9695 Nm)
- Approximate Operating Weight:** 60,320 lbs. (27,361 kg)
- APPROXIMATE BARE MACHINE WEIGHT:** 56,000 lbs. (25,402 kg)

AIR COMPRESSOR & ENGINE

- **STD:** 900 CFM @ 350 PSI @ 1800 RPM (25.5 m³/min @ 24 Bar) w/ 540 HP (403 kW) CAT C15 ACERT
- **OPT:** 1000 CFM @ 350 PSI @ 2100 RPM (28.3 m³/min @ 24 Bar) w/ 540 HP (403 kW) CAT C15 ACERT
- **OPT:** 1070 CFM @ 375 PSI @ 1800 RPM (30.3 m³/min @ 25.8 Bar) w/ 580 HP (433 kW) CAT C15 ACERT
- **OPT:** 1160 CFM @ 375 PSI @ 1800 RPM (32.6 m³/min @ 25.8 Bar) w/ 630 HP (470 kW) CAT C18 ACERT

AIR COMPRESSOR 900 CFM (25.5 m³/min) @ 350 PSI (24 Bar) with an Air ; Pressure Regulator is standard.

OPTIONAL EQUIPMENT

- Dual speed and torque rotary heads
- Compressor variable volume control
- Four leveling jack system